

ER-188

ready to use emulsion remover

DESCRIPTION

ER-188 is a full strength emulsion remover designed for fast removal of emulsions and capillary films from screens.

ADVANTAGES

- Immediately breaks down hardened emulsion
- No odor
- Non-hazardous
- Safe on all types of mesh
- Contains No VOCs

DIRECTIONS

Before using, clean the ink from the screen with non film forming ink remover such as Bio-1. As a good pre-rinse step, rinse the screen with water to remove any block-out. Spray on ER-188 in a uniform pattern onto the print contact side of the screen. In some cases better results are obtained by applying ER-188 onto both sides of the screen.

Allow to stand up to 3 minutes depending on the type and hardness of the emulsion. Remove the emulsion using a medium to high pressure cold water rinse. Flush the screen with a final rinse to remove any trace chemicals left on the screen. Allow to dry completely before recoating.

TYPICAL PRODUCT PROPERTIES

Appearance ----- Clear, colorless liquid
Odor----- None
pH -----4.5
Flash Point ----- None
Specific Gravity ----- 1.02
Weight, per U.S. gallon -----8.5 lbs.
Stability ----- Stable
DOT Shipping ----- Non-hazardous

AVAILABLE PACKAGE SIZES

55 Gallon Drum -----#01481-D5505
30 Gallon Drum -----#01481-D3004
5 Gallon Pail ----- #01481-P5010
4x1 Gallon Case -----#01481-C4201

